


MC122 Pluggable PCB Connector, Plug with Flanges



MC

DIMENSIONS/POSITIONS

MC122-508

| | | |
|--------|-------------------------|--------------------------|
| 間距 | Pitch | 5.08mm |
| 位數 | Poles | 2 ~ 20Poles |
| 塑膠本體 | Housing Material | PA 66 |
| 壓線圈 | Cage Clamp | Brass, Tin Plated |
| 端子通 | Contact | Brass, Tin Plated |
| 螺紋 | Screw Thread | M3.0, Steel, Zinc Plated |
| 電線線徑 | Wire Size | 14 ~ 24AWG |
| 最大緊固扭矩 | Tightening Torque, Max. | 4.5 Lb-in |
| 環境作業溫度 | Operating Temperature | -40° C to +105° C |

TECHNICAL DATA

| | | |
|---|--------------------------------|--------------------|
| 連接符合標準 Connection in acc. with standard EN-VDE | | |
| 額定電流 I _n | Nominal Current I _n | 10A |
| 額定橫截面 | Nominal Cross Section | 1.5mm ² |
| 最大負載電流 | Maximum load current | 10A |
| 絕緣材料 | Insulating Material | PA |
| 阻燃等級,符合UL94 Inflammability class acc. to UL94 | | V0 |
| 額定電壓,UL/CUL Nominal voltage, UL/CUL | | 250V |
| 額定電流,UL/CUL Nominal current, UL/CUL | | 10A |

